

Noxudol 700 Spray



Solventfree oil for interior treatment

General

Noxudol 700 spray is a rust preventive product free from solvents. Low viscosity binding compounds and additives have been mixed to enable application at room-temperature. This forms a soft waxy, strongly hydro fob corrosive protecting film.

Range of application

Noxudol 700 spray is a thin, penetrating rust protective compound intended for treatment of the hollow spaces of motor vehicles according to the ML method. In addition it may also be used as transport storage protection for machines, machine parts, beams, motor parts etc.

Instructions for use

High- or low pressure spraying according to the ML method for hollow spaces. Other details may be sprayed, brushed or dipped.

Package

37100095 / 500 ml

Technical data

Color:	Brown
Type of film:	Soft, waxy
Density:	900 ± 30 kg/m ³
Flash point:	> 130° C
Non volatiles:	<1 %
VOC:	<1 %
Film thickness:	40 – 60 µm
Application temperature:	20 - 50° C
Removal with:	Wash with a degreaser based on white spirit, detergent or alkali
Storing time:	12 months
Storing temperature:	5 - 35 ° C

For further information we recommend the safety data sheet or instruction on package

Issue: 2015-01-11



Auson AB, Kungsbacka, Sweden
T: +46 (0)300-56 20 00
www.auson.se

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.

Noxudol