

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

*** 1 Identification**

· **Product Identifier**

· **Trade name: Noxudol 750 Spray**

· **Product Number:** 30401

· **Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

For anti-corrosion treatment of cavities and gaps on vehicles and as general corrosion protection for equipment, tools and machines

· **Product Description**

SU21 Consumer uses: Private households (= general public = consumers)

PC6 Automotive Care Products

PC14 Metal surface treatment products, including galvanic and electroplating products

Anti corrosion oil

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Manufacturer: Auson AB

Verkstadsgatan 3

S-434 42 Kungsbacka Sweden

www.auson.se

Phone: +46 300-562000

Fax: +46 300-562001

US Distributor: Soken Trade Corporation

12055 Sherman Way

North Hollywood, CA USA

www.noxudolusa.com

Phone: (818) 308-8430

Fax: (818) 308-8428

· **Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 or Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

*** 2 Hazard(s) Identification**

· **Classification of the substance or mixture:**



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements:**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS02 GHS07 GHS08

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy

· **Hazard statements:**

Extremely flammable aerosol. Pressurized container: May burst if heated.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· **Precautionary statements:**

Do not pierce or burn, even after use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

0 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 4
Reactivity = 0

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	4	Fire = 4
REACTIVITY	0	Reactivity = 0

· **Hazard(s) not otherwise classified (HNOC):** None known

* **3 Composition/Information on Ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	30-40%
CAS: 106-97-8 RTECS: EJ 4200000	Butane ⚠ Flam. Gas 1, H220; Press. Gas, H280	~32%
CAS: 8042-47-5	Mineral Oil	20-30%
CAS: 74-98-6 RTECS: TX 2275000	Propane ⚠ Flam. Gas 1, H220; Press. Gas, H280	~8%
CAS: 61789-86-4	Sulfonic acids, petroleum, calcium salts Aquatic Chronic 4, H413	2-4%

* **4 First-Aid Measures**

- **Description of first aid measures:**
- **General information:**
Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation occurs, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting without medical advice.
May be harmful if ingested. Can cause respiratory depression and could be fatal. Call a physician or poison control center immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

* **5 Fire-Fighting Measures**

- **Extinguishing media:**
- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture:** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray**· Advice for firefighters:****· Protective equipment:**

Mouth respiratory protective device.

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

*** 6 Accidental Release Measures****· Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*** 7 Handling and Storage****· Handling****· Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities:**· Storage****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.**· Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.*** 8 Exposure Controls/Personal Protection****· Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

· **Control parameters:**

· Components with occupational exposure limits:	
64742-48-9 Naphtha (petroleum), hydrotreated heavy	
TWA	Short-term value: 600 mg/m ³ , 100 ppm Long-term value: 300 mg/m ³ , 50 ppm
106-97-8 Butane	
REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: 2370 mg/m ³ , 1000 ppm
8042-47-5 Mineral Oil	
ACGIH TLV	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³
OSHA PEL	Long-term value: 5 mg/m ³
74-98-6 Propane	
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs and BEIs book
61789-86-4 Sulfonic acids, petroleum, calcium salts	
ACGIH	Ceiling limit value: 5 mg/m ³
ACGIH TLV	Ceiling limit value: 5 mg/m ³
OSHA PEL	Ceiling limit value: 5 mg/m ³

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

· **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

· **Material of gloves:**

The selection of the suitable gloves depends on the material, and marks of quality, and varies from manufacturer to manufacturer.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

*** 9 Physical and Chemical Properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol
 Color: Light brown
 Odor: Characteristic
 Odor threshold: Not determined.

· **pH-value:** Acidic

· **Change in condition**

Melting point/Melting range: Not determined.
 Boiling point/Boiling range: -44 °C (-47 °F)

· **Flash point:** < 0 °C (< 32 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not self-igniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 0.6 Vol %
 Upper: 8.5 Vol %

· **Vapor pressure @ 20 °C (68 °F):** 2100 hPa (1575 mm Hg)

· **Density @ 20 °C (68 °F):** 0.84 g/cm³ (7.01 lbs/gal)

· **Relative density:** Not determined.

· **Vapor density:** Not determined.

· **Evaporation rate:** Not applicable.

· **Solubility in / Miscibility with:**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.
 Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 38.8 %
 VOC content: 31.1 %
 840.0 g/l / 7.01 lb/gl

· **Other information:** No further relevant information available.

*** 10 Stability and Reactivity**

· **Reactivity:** Do not expose to temperatures exceeding 50 °C/122 °F.

· **Chemical stability:** Stable under normal conditions.

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

- **Possibility of hazardous reactions:** Pressurized container: Do not pierce or burn, even after use
- **Conditions to avoid:** Heat, flame and ignition sources.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

***11 Toxicological Information**

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50/4 h	>5000 mg/l (rat)
	LC50/96 hours	>100 mg/l (Trout)
106-97-8 Butane		
Inhalative	LC50/4 h	658 mg/l (rat)
8042-47-5 Mineral Oil		
Oral	LD50	>5000 mg/kg (rat)
61789-86-4 Sulfonic acids, petroleum, calcium salts		
Oral	LD50	20000 mg/kg (rat)

- **Primary irritant effect:**
- **On the skin:**
Defats the skin; may cause cracking and dermatitis.
May cause an allergic skin reaction.
- **On the eye:** May be irritating.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories:**

· IARC (International Agency for Research on Cancer): None of the ingredients are listed.
· NTP (National Toxicology Program): None of the ingredients are listed.
· OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed.

***12 Ecological Information**

- **Toxicity:**
- **Aquatic toxicity:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy	
EC50	>100 mg/l (Green algae)
	>100 mg/l (daphnia)

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

- **Persistence and degradability:** Not easily biodegradable
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** Has the potential to bioaccumulate.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

*** 13 Disposal Considerations**

- **Waste treatment methods:**
- **Recommendation:**
Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*** 14 Transport Information**

- **UN-Number:**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name:**
- **DOT, IATA** Aerosols
- **ADR** UN1950 Aerosols
- **IMDG** AEROSOLS
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.1
- **Label:** 2.1

· **ADR, IMDG, IATA**



- **Class:** 2.1
- **Label:** 2.1
- **Packing group:** -
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

- **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

- **ADR**
- **Excepted quantities (EQ):** Code: E0
Not permitted as Excepted Quantity

- **IMDG**
- **Limited quantities (LQ):** 1L
- **Excepted quantities (EQ):** Code: E0
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

***15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **California Proposition 65:**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

· **Carcinogenic categories:**

· EPA (Environmental Protection Agency):
None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):
None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):
None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS02 GHS07 GHS08

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy

· **Hazard statements:**

- Extremely flammable aerosol. Pressurized container: May burst if heated.
- May cause an allergic skin reaction.
- May cause drowsiness or dizziness.
- May be fatal if swallowed and enters airways.

· **Precautionary statements:**

- Do not pierce or burn, even after use.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Do not spray on an open flame or other ignition source.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves.
- Contaminated work clothing must not be allowed out of the workplace.
- Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTER/doctor if you feel unwell.
- Wash contaminated clothing before reuse.
- If skin irritation or rash occurs: Get medical advice/attention.
- Do NOT induce vomiting.
- IF ON SKIN: Wash with plenty of water.
- Store locked up.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Store in a well-ventilated place. Keep container tightly closed.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/07/2016

Reviewed on 01/07/2016

Trade name: Noxudol 750 Spray

State Right to Know:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	25-50%
CAS: 106-97-8 RTECS: EJ 4200000	Butane ⚠ Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 8042-47-5	Mineral Oil	15-35%
CAS: 74-98-6 RTECS: TX 2275000	Propane ⚠ Flam. Gas 1, H220; Press. Gas, H280	5-10%
CAS: 61789-86-4	Sulfonic acids, petroleum, calcium salts Aquatic Chronic 4, H413	2-12%
All ingredients are listed.		

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*** 16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision: 01/07/2016 / 8

Abbreviations and acronyms:

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Flam. Liq. 4: Flammable liquids, Hazard Category 4
- Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106