

# Noxudol 750

## Thin ML-oil for interior treatment

### General

Noxudol 750 is a chemically active anti-corrosive compound with low surface tension, based on mineral oil, waxes, rust inhibitors and solvents. After drying it forms a waxy, moisture repellent surface. Because of the low surface tension it possesses good penetrating ability as well as the displacement of any moisture that may be present.

### Range of application

Noxudol 750 is a thin penetrating anti-corrosive that is intended for the treatment of the hollow spaces of motor vehicles according to the ML-method. In addition it may also be used for protection of iron and steel plates, beams, reserve parts, wire etc.

### Instructions for use

Start by cleaning the surface carefully, preferably with high pressure wash. Make sure the surface is dry before application. Application shall be done indoors. To apply Noxudol 750 use a high-pressure pump (airless) 1:26> with a feeding pressure of 3 – 5 bar. The material may also be applied with a low pressure pump with 1:3 (airmix). For other uses it may be sprayed, dipped or brushed on.

### Package

30300095 / 500 ml spray (12 / pack)  
30300511 / 1-lit can (12 / pack)  
30300405 / 5-lit can  
30300408 / 20-lit can  
30300701 / 60-lit drum  
30300721 / 208-lit drum

### Technical data

Color:	Light brown
Consistency:	Liquid
Type of film:	Waxy
Density at 20° C	850 ± 30 kg/m <sup>3</sup>
Dry content:	50 ± 2 %
Solvents:	White spirit
Film thickness:	40 – 80 um
Temperatur vid applicering:	15 - 25° C
Avtvättbar med:	Renox Milieu or white spirit
Lagringstid:	12 months
Lagringsförhållanden:	5 - 35° C

**For further information we recommend the safety data sheet or instruction on package**